



**FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY**

**CONTAINS:** Petroleum Distillates (8052-41-3) and Isoparaffinic Hydrocarbon (64741-66-8).

**DANGER:** Do not take internally. Avoid contact with eyes. Avoid breathing vapors. Vapor is heavier than air and may collect in low lying areas. Keep away from heat, sparks and open flame.

**FIRST AID:**

**IF EYE CONTACT:** Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

**IF SKIN CONTACT:** Wash with soap and water. If irritation persists, seek medical attention.

**EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops, give artificial respiration.

**IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

**HMS RATING:** Health, 1; Flammability, 3; Reactivity, 0; Personal Protection, B.

**HANDLING AND STORAGE:**

Keep container closed except when in use. Do not store in unmarked containers. Store in a cool, dry place. Do not cut or weld on or near container, even when empty.

For further information,  
consult Material Safety Data Sheet



**BATTERY TERMINAL PROTECTOR**  
272305

Long-Term  
Corrosion Preventative

**DANGER:** FLAMMABLE LIQUID.  
VAPOR HARMFUL.  
HARMFUL OR FATAL IF SWALLOWED.  
KEEP OUT OF REACH OF CHILDREN  
SEE OTHER CAUTIONS ON SIDE PANEL.  
NET CONTENTS: 5 GALLONS

**TERAND**  
INDUSTRIES, INC.

P.O. Box 667770 • Pompano Beach, FL 33066  
www.terandstore.com

**No Chlorinated Solvents  
(No 1,1,1-Trichloroethane)**

BATTERY TERMINAL PROTECTOR is a long-term corrosion preventative that:

- Provides an airtight waterproof seal
- Curtails battery leakage
- Extends battery life

The coating will not crack or peel even under severe flexing.

Use on battery terminals, cables, carriers or hold downs.

Excellent for batteries that are used infrequently or put into storage.

**USEFUL ON:** Auto, boat, truck, fork-lift, golf cart and generator batteries.

**DIRECTIONS:**

Coating is most effective if surface is first prepared clean and dry. Spray an even coat over entire surface. For more severe conditions, a second coating can be applied within a few minutes. Allow several hours to set up to tack-free film. Coating may be removed with mineral spirits.