Permatex, Inc. 10 Columbus Blvd. Hartford, CT 06106 USA Telephone: 1-87-Permatex (877) 376-2839 Emergency: 800-255-3924 International Emergency: 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name:HIGH TEMPERATURE SLEEVE RETAINER 50MLItem No:64050Product Type:Anaerobic

2. COMPOSITION/INFORMATION ON INGREDIENTS			
Component	Weight%	ACGIH TLV: TWA	OSHA PEL:
DIMETHACRYLATE ESTER 27813-02-1	30-40	Not listed	Not Listed
POLYURETHANE METHACRYLATE RESIN 68400-67-9	5-20	Not listed	Not Listed
ACRYLIC ACID 79-10-7	<10	2 ppm TWA	10 ppm TWA; 30 mg/m ³ TWA
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	<3	Not listed	Not Listed
AROMATIC AMINE 609-72-3	<1	Not listed	Not Listed
ALKYL TOLUIDINE 613-48-9	<1	Not listed	Not Listed

3. HAZARDS IDENTIFICATION

Toxicity:

May cause eye and skin irritation. May cause nose, throat and respiratory irritation. Ingestion may irritate digestive tract and cause nausea, vomiting and diarrhea. High concentrations may cause central nervous system (CNS) depression. May cause skin sensitization. Eye and skin contact, ingestion, inhalation

Primary Routes of Entry: Signs and Symptoms of Exposure:

May cause redness to eyes and irritation to nasal passages. Repeated skin contact may cause allergic skin reactions. Ingestion may cause nausea and vomiting. Inhalation overexposure may cause irritation, coughing and flu-like symptoms.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
ACRYLIC ACID	<10		A4 - Not Classifiable	Group 3 Monograph 71,
79-10-7			as a Human	1999; Supplement 7, 1987;
			Carcinogen	Monograph 19, 1979

Medical Conditions Recognized as Being Aggravated by Exposure: Preexisting pulmonary and dermatological disorders.

4. FIRST AID MEASURES

Ingestion: Inhalation:

Skin Contact: Eye Contact: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.
Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed.
Obtain medical attention.
Wash off with soap and water. If skin irritation persists, call a physician.
In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): Recommended Extinguishing Media: Special Fire-Fighting Procedures: Hazardous Products of Combustion: Unusual Fire/Explosion Hazards:

Lower Explosive Limit:

>200°F TCC

Water fog, carbon dioxide, foam, dry chemical. Firefighters should wear self-contained breathing apparatus. Oxides of carbon None.

Not determined

5. FIRE FIGHTING MEASURES

Upper Explosive Limit:

Not determined

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage:Store below 100 degrees F.Handling:Avoid prolonged skin contact. Keep away from eyes. Do not inhale vapors.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:	Safety glasses.
Skin:	Rubber or plastic gloves.
Ventilation:	General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
Respiratory Protection:	An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Green liquid
Odor:	IRRITATING
Boiling Point:	Not determined
pH:	Does not apply
Solubility in Water:	Slight
Specific Gravity:	1.1
VOC Content(Wt.%):	<2%
Vapor Pressure:	<10 mm Hg @ 25°C
Vapor Density (Air=1):	Heavier than air
Evaporation Rate:	Not Determined
-	

10. STABILITY AND REACTIVITY

Chemical Stability: Hazardous Polymerization: Incompatabilities: Conditions to Avoid: Hazardous Products of Combustion: Stable at normal conditions WILL NOT OCCUR. Strong oxidizers, free radical initiators, inert gases Heat. Oxides of carbon

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal:Disposal should be made in accordance with federal, state and local regulations.US EPA Waste Number:NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Unrestricted
None
None
None

ΙΑΤΑ

Proper Shipping Name:	Not regulated
Class or Division:	None
UN/ID Number:	None

IMDG

Proper Shipping:	Unrestricted
Hazard Class:	None
UN Number:	None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

ACRYLIC ACID, DIMETHYLBENZYL HYDROPEROXIDE

CALIFORNIA PROP 65: No California Prop 65 chemicals are known to be present.

TSCA Inventory Status: Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating:HEALTH 2, FLAMMABILITY 1, REACTIVITY 1.Estimated HMIS Classification:HEALTH 2, FLAMMABILITY 1, PHYSICAL HAZARD 0NFPA is a registered trademark of the National Fire Protection Assn.HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By:	Denise Boyd, Manager-Environmental, Health & Safety	Revision Date: February/28/2008
Company:	Permatex. Inc. 10 Columbus Blvd. Hartford, CT USA 0610	6 Revision 3
		Number:
Telephone No.:	1-87-Permatex (877) 376-2839	