

Same
Formula
NEW LOOK!!

FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY

DANGER: Contains Isoparaffinic Hydrocarbon (64742-48-9) and Polydimethylsiloxane (63148-62-9). Do not take internally. Avoid contact with eyes. Avoid breathing vapors. Vapor is heavier than air and may collect in low lying areas.

FIRST AID:

IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

IF SKIN CONTACT: Wash with soap and water. If irritation persists seek medical attention.

EXCESSIVE INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

IF INGESTED: Do not induce vomiting. Seek medical attention immediately.

HMIS RATING: Health, 1; Flammability, 3; Reactivity, 0; Personal Protection, B.

HANDLING AND STORAGE:

Keep container closed except when in use. Do not store in unmarked containers. Store in a cool, dry place. Do not cut or weld on or near this container even when empty.

For further information, consult
Material Safety Data Sheet.



SILICONE LUBRICANT FOOD GRADE

259005

Dry Lubricant and
Release Agent



TECHNO SOLUTIONS WORLD

PO Box 375122 Cayey, PR 00737-5122
P. 787-738-0087, 0088 Fx. 1-888-456-0656
www.technosw.com , sales@technosw.com

- A heat stable (from -40°F to +285°F), dry silicone mold release.
- Quickly dries to a clear, non-staining, waterproof film.
- Stops sticking, squeaking and binding.
- Speeds production.
- Reduces clean-up time.
- Will not gum up or run off.
- When dry, leaves a pure silicone film having the highest acceptance rating by the USDA.
- Ends poly, cellophane, paper or wax build-up on food packaging and processing equipment.
- Keeps food from sticking to ovens, conveyors, slicing machines, grinders, saws, chain hooks, etc.
- Used on heat sealing equipment in the meat, dairy, milk and food processing industries.

DIRECTIONS:

1. Clean surface thoroughly before coating.
2. Do not thin with any other chemical.
3. May be applied by dipping or spraying.
4. When spraying, use either airless or compressed air sprayer and apply lightly and evenly.
5. Always keep container closed when not in use to prevent evaporation or contamination.