

Designed and manufactured in an environmentally conscious manner from materials that are biodegradable, toxin free, petroleum distillate free, VOC compliant and contain no ozone depleters.

**WARNING:** Contains Soybean Oil (8001-22-7), Citrus Terpene (5989-27-5). Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

**FIRST AID:**

**IF EYE CONTACT:** Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

**EXCESSIVE SKIN EXPOSURE:** Wash with soap and water. If irritation persists seek medical attention.

**EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

**IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

**HMIS RATING:** Health, 1; Flammability, 2; Reactivity, 0; Personal Protection, B.

**HANDLING AND STORAGE:** Keep container closed except when in use. Do not store in unmarked containers. Store in a cool, dry place. Do not cut or weld on or near this container even when empty.

For further information consult  
Material Safety Data Sheet.



**TERAND INDUSTRIES, INC.**  
P.O. Box 667770 • Pompano Beach, FL 33066  
[www.terandstore.com](http://www.terandstore.com)



# NATRA-LUBE ORGANIC PENETRATING OIL

**LOW ODOR**

**RENEWABLE RESOURCES**

- **NEVER DRY FILM**
- **QUICK PENETRATING ACTION**

**WARNING:** FLAMMABLE  
SEE OTHER CAUTIONS ON SIDE PANEL

NET CONTENTS: 5 GALLONS

Designed and manufactured in an environmentally conscious manner from materials that are biodegradable, toxin free, petroleum distillate free, VOC compliant and contain no ozone depleters.

Contains no silicones or harsh solvents, which can affect plastics, lacquers, insulation and paint. Never-dry oil film lubricates parts, reducing friction and wear, to ensure free and easy movement over a broad temperature range.

**DIRECTIONS:**

Saturate part to be loosened and allow product to penetrate for a moment before attempting to break free. For heavily encrusted pieces a wire brush may be used to help remove corrosion. Apply a final coat to all parts prior to reassembly.

To learn more about these products  
go to: [www.GOODEARTHLINE.COM](http://www.GOODEARTHLINE.COM)