MATERIAL SAFETY DATA SHEET
This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUF	ACTU	<b>RER'S INFORMATI</b>	ON				
PA Rating: Health-1; Flammability-1; Reactivity-0; Special - HMIS Rating: Health-1; Flammability-1; Reactivity-0; Personal Protection-B							
Manufacturer's Name: AMREP, INC.	DO	DOT Hazard Classification: Non-Hazardous					
Address: 990 Industrial Park Dr.	lde	Identity (trade name as used on label):					
Marietta, GA 30062		MISTY MOLY GREASE					
Date Prepared: 11/03/93 Prepared By: ES/DL	MS	MSDS Number: RL 728 Revision - 2					
Information Calls: (770)422-2071 EMERGENCY RESPONSE NUMBER: 1(800)255-3924		NOTICE: JUDGMENT BASED ON INDIRECT TEST DATA					
SECTION 1 - MATERIAL IDEN	JTIFIC	ATION AND INFOR	ΜΔΤΙΩΝ				
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES	*****	CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen	
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		C/10 Humbon	III LIST	(ppm)	TLV (ppm)	Ref. Source **	
PETROLEUM OIL MIXTURE		8002-05-9	No	5mg/M3	5mg/M3	d	
					TWA for oil		
				mist	mist		
WARNING: This product contains a chemical or chemicals known	to						
the State of California to cause cancer.							
SECTION 2 - PHYSICAL/C	неми	CAL CHADACTED!	STICS		1		
Boiling Point: N/A		cific Gravity (H2O=1):					
Vapor Pressure: PSIG @ 70°F (Aerosols): N/A	Van	Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): <0.01					
Vapor Density (Air = 1): 12		Evaporation Rate ( = 1): N/A					
Solubility in Water: Negligible		Water Reactive: No					
Appearance and Odor: Grey/black gel with oil odor.							
SECTION 3 - FIRE AND	FXPI	OSION HAZARD DA	ΤΔ				
LAMMABILITY as per USA FLAME Auto Ignition Temperature Flammability Limits in Air by % in Volume:							
PROJECTION TEST (aerosols) N/A N/A	% LEL: N/D % UEL: N/D						
FLASH POINT AND METHOD USED (non-aerosols): >400°F COC	EXT	INGUISHER MEDIA:				e. foam. water.	
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatu			_ ,	(		-,,	
Unusual Fire & Explosion Hazards: Empty containers may retain product re	sidue i	ncluding flammable or	explosive v	apors. Do no	t cut, drill, grine	d or weld on or	
near full, part full or empty drum.							
SECTION 4 - REAC							
STABILITY [X] STABLE [ ] UNSTABLE	_	ZARDOUS POLYMERI			X] WILL NOT	OCCUR	
ncompatibility (Mat. to avoid): Chlorine or oxygen.  Conditions to Avoid: Oxidizing atmospheres.							
Hazardous Decomposition Products: Thermal: unidentified organics. Oxida							
SECTION 5 - HEALTH HAZARD DATA							
PRIMARY ROUTES OF ENTRY: [ ]INHALATION [ ]INGESTION [ X ] SKIN ABSORPTION [ ] EYE [ ] NOT HAZARDOUS							
ACUTE EFFECTS							
Inhalation: Not expected to be a problem. Massive exposure to vapors or fume	es may	cause headaches, diz	ziness, and	d/or drowzines	s.		
Eye Contact: May cause irritation. Skin Contact: May cause irritation.							
Ingestion: May cause vomiting, nausea, diarrhea.							
CHRONIC EFFECTS: None noted.							
Medical Conditions Generally Aggravated by Exposure: Dermatitis.							
EMERGENCY FIRE	ST All	D PROCEDURES					
Eye Contact: Wash with large amounts of water. If irritation persists, call a phy							
Skin Contact: Remove contaminated clothing. Wash with soap and water.	-						
Inhalation: Remove to fresh air.							
Ingestion: DO NOT INDUCE VOMITING. Give 3-4 glasses of water. Seek m	nedical	attention.					
SECTION 6 - CONTROL A			IRFS				
Respiratory Protection (specify type): None required.		10.201112 1112/101	J. (				
Protective Gloves: Oil resistant types.	Fve	Protection: Splash g	nnales or s	afety glasses			
Ventilation Requirements: None required in excess to normal ventilation.	<sub> </sub> _yc	Trottotion: opiasing	oggics or c	dicty glasses.			
Other Protective Clothing & Equipment: Oil resistant apron.							
Hygienic Work Practices: Do not work in oil soaked clothing. Wash after han	dling						
		CVEE HVIIDI INO V	ND HEE				
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE  Stone To Be Taken If Material is Spilled Or Belegged. Ston flow dilks spill eliminate all ignition sources, about no inert material and across up.							
Steps To Be Taken If Material Is Spilled Or Released: Stop flow, dike spill, eliminate all ignition sources, absorb on inert material and scrape up.							
Waste Disposal Methods: Dispose of in accordance with local, state and fede				ر المصم م	V	mtainar-	
<b>Precautions To Be Taken In Handling &amp; Storage:</b> Avoid prolonged exposure closed. Shelf life one year.	to mis	and vapors. Avoid fla	mes, spark	s and not surf	aces. Keep co	mainers	
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Empty containers may contain explosive gas.							
rement		pty contamions illa	Joinani C	APICOITO GUO.			

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

\*\* Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only