MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFACTURER'S INFORMATION					
	HMIS Rating: Health-1; Flammability-3; Reactivity-0; Personal Protection-B				
,	DOT Hazard Classification: ORM-D				
Address: 990 Industrial Park Drive I Marietta, GA 30062	Identity (trade name as used on label): MISTY ODOR NEUTRALIZER PLUS+				
	MSDS Number: A00207 Revision-4				
Information Calls: (770)422-2071	NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA				
EMERGENCY RESPONSE NUMBER: 1(800)255-3924					
SECTION 1 - MATERIAL IDEN	ITIFICATION AND INF	ORMATI	ON		
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES	CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		III LIST	(ppm)	TLV (ppm)	Ref. Source **
ACETONE	67-64-1	No	1000	750	d
ISOBUTANE / PROPANE BLEND	75-28-5	No	800	800	d
	74-98-6	No	1000	1000	d
OF ATION A PUNCION VOLUMENTAL AND A STEP INTERES					
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS Boiling Point: N/A Specific Gravity (H2O=1): Concentrate Only = 0.8					
piling Point: N/A Specific Gravity (H2O=1): Concentrate Only = 0.8 Vapor Pressure: PSIG @ 70°F (Aerosols): 50-60 Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A					
	Evaporation Rate (= 1): N/E				
	Water Reactive: No				
Appearance and Odor: Clear liquid with fragrance.					
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA					
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols):					
flame projection with spray through cap: projection greater than 18" with	N/E		% LEL: 1	Ã	% UEL: N/E
flashback: Categorized as EXTREMELY FLAMMABLE					
FLASH POINT AND METHOD USED (non-aerosols): N/A SPECIAL FIRE FIGHTING PROCEDURES: Provide shielding for personnel. Wear self-					
EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water. contained breathing apparatus. Cool containers with water fog to prevent rupturing & spewing					
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 120°F or the container may rupture.					
SECTION 4 - REACTIVITY HAZARD DATA					
STABILITY [X] STABLE [] UNSTABLE HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR					
Incompatibility (Mat. to avoid): Alkalis, oxidizing materials, amines. Conditions to Avoid: Open flame, welding arcs, heat.					
Hazardous Decomposition Products: CO, CO2.					
SECTION 5 - HEALTH HAZARD DATA					
PRIMARY ROUTES OF ENTRY: [X] INHALATION [] INGESTION [] SKIN ABSORPTION [] EYE [] NOT HAZARDOUS					
ACUTE EFFECTS Vapor concentrations around 1000 ppm may cause slight transient irritation to the upper respiratory tract.					
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.					
Eye Contact: Irritation. Skin Contact: May cause slight irritation.					
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.					
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause mucous membrane irritation, overnight headache, and general weakness.					
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.					
EMERGENCY FIRST AID PROCEDURES					
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.					
Skin Contact: Wash with soap and water. If irritated, seek medical attention.					
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.					
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of w		nedical at	tention.		
SECTION 6 - CONTROL A					
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use			S. Bureau of N	Mines for organ	nic vapor.
Protective Gloves: Latex, if skin easily irritated.					
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.					
Other Protective Clothing & Equipment: None					
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.					
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE					
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. DO NOT FLUSH TO SEWER.					
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure the	•				
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 120°F.					
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. Remove ignition sources.					

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only