



## FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY

**DANGER:** Contains Mineral Oil (8042-47-5), Octamethylcyclotetrasiloxane (556-67-2), Decamethylcyclopentasiloxane (541-02-6), and Dipropylene Glycol Monomethyl Ether (34590-94-8). Do not take internally. Use only in a well ventilated area. Avoid contact with eyes or prolonged contact with skin. Avoid contamination of food. Do not expose to heat or store at temperatures above 120°F.

### FIRST AID:

**IF EYE CONTACT:** Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists seek medical attention.

**IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention.

**EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

**IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

**HMIS RATING:** Health, 1; Flammability, 1; Reactivity, 0; Personal Protection, B.

### HANDLING AND STORAGE:

Keep container closed except when in use. Do not store in unmarked containers. Store in a cool, dry place.

For further information, consult Material Safety Data Sheet.



## PENETRANT LUBRICANT DEMOISTURANT PROTECTANT

220905

Non-Chlorinated  
All Purpose Mechanics  
Lubricant  
Non-Flammable  
Non-Conductive



**TECHNO SOLUTIONS WORLD**

PO Box 375122 Cayey, PR 00737-5122  
P. 787-738-0087, 0088 Fx. 1-888-456-0656  
[www.technosw.com](http://www.technosw.com), [sales@technosw.com](mailto:sales@technosw.com)

**NO Chlorinated Solvents**  
**(NO 1,1,1-Trichloroethane)**  
**(NO Perchloroethylene)**  
**(NO Methylene Chloride)**

### HIGH DIELECTRIC STRENGTH

**NUT and BOLT LOOSENER** — Rapidly penetrates through rust and corrosion.

**WATER DISPLACER** — Displaces moisture from electrical parts. Prevents malfunction to electrical equipment exposed to high humidity.

**LUBRICANT** — Assures free and easy movement of parts.

**ANTI-CORROSIVE COATING** — Leaves a protective film that seals out future rust, corrosion and the harmful effects of moisture.

**USES:** Motors, relays, switches, plugs, reostats, electronic and electrical assemblies, parking and water meters, marine equipment, vending machines, vehicles, appliances, tools, machinery, generators, batteries, chargers, jigs, fixtures, fans, battery terminals, motor-cycles, blowers, hoists, overhead doors.

### DIRECTIONS:

1. For best performance and fullest protection, first clean object with degreaser solvent to remove grease, oil and debris. This will prevent material from becoming contaminated, especially when used in a dip tank.
2. Apply as a spray, brush on, or use in a dip tank.
3. Allow wetted-out rusted parts to be immersed in solution for several minutes.
4. Always keep container closed to prevent evaporation or contamination.