MATERIAL SAFETY DATA SHEET

COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

SECTION I · PRODUCT IDENTIFICATION

Product Name: Penetrant, Lubricant, Demoisturant, Protectant Product Number: 2-209 Product Type: Bulk Liquid Supplier's Name: Terand Industries, Inc.

Formula: Proprietary Date Prepared: 02/07/08 Emergency Phone: (800) 535-5053 Information Phone: (954) 974-5440 HMIS Rating: 0-Minimal 1- Slight 2- Moderate 3- Serious 4- Extreme

Supplier's Address: P.O. Box 667770, Pompano Beach, FL 33066

Shipping Description: Oils, Lubricating, N.O.I. (not regulated under 49 CFR by DOT)

SECTION II · INGREDIENTS						
CAS #	%WT	313/Chem	Skin	Carcinogen	PEL	TLV/TWA
8042-47-5	40-50	NO	NO	NO	5mg/M ³	5mg/M ³
556-67-2	01-05	NO	NO	NO	NE	10 ppm*
541-02-6 34590-94-8	01-05 01-05	NO NO	NO NO	NO NO	NE 100 ppm	10 ppm* 100 ppm
	8042-47-5 556-67-2	CAS # %WT 8042-47-5 40-50 556-67-2 01-05 541-02-6 01-05	CAS # %WT 313/Chem 8042-47-5 40-50 NO 556-67-2 01-05 NO 541-02-6 01-05 NO	CAS # %WT 313/Chem Skin 8042-47-5 40-50 NO NO 556-67-2 01-05 NO NO 541-02-6 01-05 NO NO	CAS # %WT 313/Chem Skin Carcinogen 8042-47-5 40-50 NO NO NO 556-67-2 01-05 NO NO NO 541-02-6 01-05 NO NO NO	CAS # %WT 313/Chem Skin Carcinogen PEL 8042-47-5 40-50 NO NO NO 5mg/M ³ 556-67-2 01-05 NO NO NO NE 541-02-6 01-05 NO NO NO NE

*Manufacturer's recommended TWA exposure limit.

SECTION III · PHYSICAL DATA

Vapor Density (Air=1): >1 Specific Gravity (H2O=1)@75°F: 0.84

Boiling Point: ~500° F Solubility In Water: Slight Appearance/Odor: Brownish liquid, Mild solvent odor. Total VOC %: ~ 3.35%

SECTION IV · FIRE AND EXPLOSION DATA

Flash Point: >200°F (T.O.C.) Extinguishing Media: Water Fog, Foam, CO2. Dry Media.

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing. Unusual Fire and Explosion Hazards: Exposure to temperature above 120°F may cause bursting

SECTION V · REACTIVITY DATA

Hazardous Polymerization: Will not occur.

Stability: Material Stable. Incompatibility: Avoid contact with strong oxidizing agents. Hazardous Decomposition Products: Carbon Monoxide, Carbon Dioxide.

SECTION VI · STORAGE AND HANDLING

KEEP OUT OF REACH OF CHILDREN.

For Industrial and Institutional use only. Store in a cool, dry area away from heat or open flame. Do not store at temperatures above 120°F.

SECTION VII · HEALTH AND FIRST AID

PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:

Eyes: May cause slight irritation but does not injure eye tissue.

Skin: Frequent or prolonged contact may cause irritation.

Inhalation: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, dizziness, nausea and other central nervous system effects. Prolonged exposure may affect the liver.

Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis.

FIRST AID PROCEDURES:

Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists seek medical attention.

Skin: Wash with soap and water. If irritation persists seek medical attention.

Inhalation: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

Ingestion: Do not induce vomiting. Seek medical attention immediately.

SECTION VIII · SPECIAL PROTECTION DATA

Respiratory Protection: None needed for proper use in accordance with label directions. Ventilation: Provide local exhaust to keep concentration of Section II ingredients below acceptable limits. Protective Gloves: Use chemical resistant gloves if hand contact will be made. Eye Protection: Always wear safety glasses or chemical proof goggles when working with chemicals.

SECTION IX · SPILL OR LEAK PROTECTION

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK: Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with suitable absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws. WASTE DISPOSAL METHOD: Consult Federal, State and local authorities for approved procedures.

N/A= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · <=LESS THAN · >=MORE THAN

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.

HEALTH: 1 FIRE: 1 REACTIVITY: 0 Personal Protection : B