Eliminates calcium build-up from moisture in air lines. Dissolves sludge, dirt and dust accumulation. Lubricates and protects all moving parts. Restores air tools to peak power and RPM's. Use regularly for preventative maintenance to cut downtime and costly repairs.

**USE FOR CLEANING & LUBRICATING:** Air Operated Tools, Sanders, Jackhammers, Drills, Saws, Impact Wrenches, Polishers, Grinders, Air Operated Motors

## **DIRECTIONS:**

SHAKE WELL BEFORE USING. For interior application, insert extension tube into actuator orifice prior to use.

- 1. Spray into all openings including air inlet connection.
- 2. Allow product to penetrate for several seconds.
- 3. Run air tool at maximum RPM for 30 seconds.
- 4. Repeat above for severe conditions.
- 5. For long term tool storage, repeat directions 1 through 3.







**DANGE:** Contains Hydrocarbon well-ventilated area. Contents under medical temperatures above 120°F.

Isoparaffinic FIRST AID: IF EYE CONTACT: (64742-66-8), Flush with large amounts of cool Liquefied Petroleum Gas (68476- running water for at least 15 minutes 86-8). Mineral Oil (8042-47-5), and while holding upper and lower lids Isopropanol (67-63-0). Use only in a open. If irritation persists seek attention. IF pressure. Do not puncture or CONTACT: Wash with soap and incinerate container. Avoid contact water. If irritation persists seek with eyes or prolonged contact with medical attention. EXCESSIVE skin. Avoid contamination of food. Do INHALATION: Remove to fresh air. not expose to heat or store at Seek medical attention immediately. If breathing stops give artificial respiration. IF INGESTED: Do not induce vomiting. Seek medical attention immediately.

For further information consult Material Safety Data Sheet.

## **KEEP OUT OF REACH** OF CHILDREN







## AIR TOOL .EANER and UBRICANT

Cleans, Lubricates, Reconditions

Eliminates Moisture

23912

NEW LOOK!

**Prevents Rust & Corrosion** 

Extends Life of Air Tools

DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. CONTENTS UNDER PRESSURE. SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 12 OZ. (340 Grams)