



PRODUCT SALES SHEET

G00726

Red Grease NLGI #2

Greases



TECHNO SOLUTIONS WORLD

PO Box 375122 Cayey, PR 00737-5122
P. 787-738-0087, 0088 Fx. 1-888-456-0656
www.technosw.com , sales@technosw.com

Features

- 550+ Dropping Point, Non-Melt Grease
- 65 Timken OK Load
- Good Resistance to Environmental Conditions
- Adhesive & Cohesive Properties

Description

Red Grease is an all purpose non-melt grease especially formulated with extreme pressure and anti-wear additives to provide heavy duty service. It is one of very few greases able to withstand heavy shock load and impact pressures of 65 Timken load capabilities. This product has excellent adhesive and cohesive properties. It resists most acids, weather, dirt, salt-spray, steam and oxidation. Our product protects equipment indoors or outdoors even under high temperatures and heavy loads.

TECHNICAL INFO:		
Physical Properties	Appearance	
	Color	Red
	Odor/Fragrance	Petroleum
	pH	N/A
	Spray Pattern	N/A
Environmental Profile	Glycol Ether Content	None
	Biodegradability	No
	Chlorinated Solvents	None
	Green Status	None
	Recyclable Packaging	Yes
Regulatory Profile	% VOC By Weight	1.0
	VOC Restricted Regions	None
	Food Processing Suitability	H2
	EPA #	N/A
	Flammability per CPSC	N/A
	Flash Point	> 400° F



Packages Available:

14 oz

7 lb

45 lb

120 lb
420 lb

