MATERIAL SAFETY DATA SHEET
This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFA	CTU	RER'S INFORMATION	N			
NFPA Rating: Health-3; Flammability-1; Reactivity-0; Special- COR	HMIS Rating: Health-3; Flammability-1; Reactivity-0; Personal Protection-E					
Manufacturer's Name: AMREP, INC.	DOT Hazard Classification: Corrosive Material, 8					
Address: 990 Industrial Park Drive	Identity (trade name as used on label):					
Marietta, GA 30062 MISTY SECURE						
Date Prepared: 10/17/06 Prepared By: TR/IB	MSDS Number: B00930 Revision –9					
Information Calls: (770)422-2071 EMERGENCY RESPONSE NUMBER: 1(800)255-3924 NOTICE: JUDGMENT BASED ON INDIRECT TEST DATA						
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES		CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater) HYDROCHLORIC ACID		7647-01-0	III LIST Yes	(ppm) 5	TLV (ppm) 5	Ref. Source **
THE DROGHED ROLD		7047-01-0	165	3	3	u
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS						
Boiling Point: approximately 212°F Specific Gravity (H2O=1): 1.05						
Vapor Pressure: PSIG @ 70°F (Aerosols): N/A	Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A					
Vapor Density (Air = 1): Not known	Evaporation Rate (water= 1): 1					
Solubility in Water: Completely Soluble Water Reactive: None						
Appearance and Odor: Clear, blue and "bodied" liquid with acrid-mint odor						
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA						
N/A	Auto Ignition Temperature N/A Flammability Limits in Air by % in Volume: % LEL: N/A % UEL: N/A					
FLASH POINT AND METHOD USED (non-aerosols): Not known SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved breathing apparatus & full protective gear when fighting fires. Spray containers with water to keep cool & prevent						
EXTINGUISHER MEDIA: Foam, dry chemical, CO ₂ or water ruptures.						
Unusual Fire & Explosion Hazards: Avoid exposure to metals, oxidants which might product flammable hydrogen gas.						
SECTION 4 - REACTIVITY HAZARD DATA STABILITY [X] STABLE [] UNSTABLE HAZARDOUS POLYMERIZATION [] WILL [X]WILL NOT OCCUR						
Incompatibility (Mat. to avoid): Bases, metals, mercuric sulfate, carbides of Conditions to Avoid: Contact with strong bases can cause violent reaction						
calcium, cesiam, rubidium. generating large amounts of heat.						
Hazardous Decomposition Products: Products of combustion are toxic. Byproducts are vapors of hydrochloric acid which are corrosive & highly irritating						
SECTION 5 - HEALTH HAZARD DATA						
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION [X]SKIN ABSORPTION [X]EYE []NOT HAZARDOUS						
ACUTE EFFECTS						
Inhalation: Irritant causing burning, choking, coughing, headache.						
Eye Contact: Corrosive, severe burns & permanent damage including blindness. Skin Contact: Burning, irritation, dermatitis.						
Ingestion: Unlikely route-causes severe burns mucosal membranes and irritation to digestive trace.						
CHRONIC EFFECTS: None known.						
Medical Conditions Generally Aggravated by Exposure: Skin, eye, mucous membrane irritation.						
EMERGENCY FIRST AID PROCEDURES						
Eye Contact: Wash eyes for 15 minutes. Get immediate medical attention.						
Skin Contact: Remove contaminated clothing, wash skin with water for 15 minutes.						
Inhalation: Move to fresh air. Get medical attention.						
Ingestion: DO NOT INDUCE VOMITING. Drink 3 to 4 glasses of milk or water. Get immediate medical attention.						
SECTION 6 - CONTROL AND PROTECTIVE MEASURES Respiratory Protection (specify type): NIOSH approved self-contained breathing apparatus when use concentrations exceed 100 ppm HCI						
vapors.						100 ppm HCI
rotective Gloves: Rubber, Neoprene or Nitrile. Eye Protection: Chemical goggles or face shield.						
Ventilation Requirements: As necessary to maintain air concentration below 5 ppm at all times.						
Other Protective Clothing & Equipment: Neoprene or PVC rain suit & boots in case of fire. Safety showers & eyewash stations should be available.						
Hygienic Work Practices: Wash hands after use. Do not eat, drink or smoke in immediate area.						
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE						
Steps To Be Taken If Material Is Spilled Or Released: Contain fluid by diking	g. Nei	ıtralize with soda ash or	baking so	oda.		
Waste Disposal Methods: Neutralized material may be washed down the sewer. Absorbed material to be boxed and disposed of in compliance with local, state and federal regulations.						
Precautions To Be Taken In Handling & Storage: Store in closed labeled containers. Keep in cool, metal free area for not more than one year.						
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Do not store near strong alkalies or other reactive materials.						

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only