# Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 11/13/2008 Reviewed on 11/13/2008

#### 1 Identification of substance

Trade name: GOOD GRIP CLEAR

**Product code:** 0000160081

Manufacturer/Supplier: SEYMOUR OF SYCAMORE

917 Crosby Avenue Sycamore, IL 60178

(815)-895-9101, www.seymourpaint.com

Emergency information: CHEMTEL 1-800-255-3924, 813-248-0585 \*if located outside the U.S.\*



# 2 Composition/Data on components

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous	Dangerous components:		
67-64-1	Acetone	38.45%	
74-98-6	propane	13.87%	
1330-20-7	xylene (mix)	9.38%	
106-97-8	n-butane	8.15%	
	methyl isobutyl ketone	6.24%	
100-41-4	ethyl benzene	2.34%	
108-65-6	PM acetate	1.91%	
1317-65-3	Calcium Carbonate	1.58%	

### 3 Hazards identification

**Hazard description:** 

**K** 

Harmful

Extremely flammable

**Physical dangers:** Extremely flammable.

Harmful by inhalation. Irritating to eyes.

Keep out of the reach of children.

**Effects of chronic** 

overexposure:

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be

harmful or fatal.

**NFPA ratings (scale 0 - 4):** Health =

Fire = 4

Reactivity = 3

HMIS-ratings (scale 0 - 4): Health=

Health=

Fire= 4 Physical Hazard= 3

### 4 First aid measures

**General information:** Symptoms of poisoning may occur even after several hours. Medical observation for at least 48 hours

after the accident is recommended.

After inhalation: Supply fresh air. If necessary, provide artificial respiration. Keep patient warm. Consult doctor if

symptoms persist.

**After skin contact:** Remove contaminated clothing. Wash exposed area with soap and water.

**After eye contact:** Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist,

consult a doctor.

**After swallowing:** Contact physician or poison control center.

# 5 Fire fighting measures

**Extinguishing agents:** CO2, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant

foam.

**Protective equipment:** A respiratory protective device may be necessary.

#### 6 Accidental release measures

Personal safety

**precautions:** Wear protective equipment. Keep unprotected persons away.

**Environmental safety** 

**precautions:** Do not allow product to reach sewage systems or ground water.

(Contd. on page 2)

(Contd. of page 1)

## **Material Safety Data Sheet** acc. to ISO/DIS 11014

Printing date 11/13/2008 Reviewed on 11/13/2008

Trade name: GOOD GRIP CLEAR

Measures for cleaning/

collecting: Ensure adequate ventilation.

7 Handling and storage

Fire/explosion protection: Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic

discharges.

**Storage requirements:** Observe pressurized container storage regulations. Consult with your local authorities.

	8 Exposure controls and personal protection:	
Components with limit values that require monitoring at the workplace		nents with limit values that require monitoring at the workplace:
67-64-1 Acetone		
	PEL	2400 mg/m <sup>3</sup> , 1000 ppm

REL	$590 \text{ mg/m}^3$ , 250 ppm
TLV	Short-term value: 1782 mg/m <sup>3</sup> , 750 ppm
	Long-term value: 1188 mg/m <sup>3</sup> , 500 ppm
	BEI

Q Exposure controls and personal protection.

74-98-6 propane
-----------------

PEL	1800 mg/m³, 1000 ppm
	$1800 \text{ mg/m}^3$ , $1000 \text{ ppm}$
	Varies mg/m³, 1000 ppm

# 1330-20-7 xylene (mix)

435 mg/m <sup>3</sup> , 100 ppm
Short-term value: 655 mg/m <sup>3</sup> , 150 ppm
Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
Short-term value: 651 mg/m <sup>3</sup> , 150 ppm
Long-term value: 434 mg/m <sup>3</sup> , 100 ppm
BEI

# 106-97-8 n-butane

REL	1900 mg/m³, 800 ppm
	Varies mg/m³, 1000 ppm

# 108-10-1 methyl isobutyl ketone

PEL	$410 \text{ mg/m}^3$ , $100 \text{ ppm}$
REL	Short-term value: 300 mg/m <sup>3</sup> , 75 ppm
	Long-term value: 205 mg/m <sup>3</sup> , 50 ppm
	Short-term value: 307 mg/m³, 75 ppm Long-term value: (205) NIC-123 mg/m³, (50) NIC-30 ppm
	BEI;NIC-A3

# 100-41-4 ethyl benzene

PEL	435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm
	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 543 mg/m <sup>3</sup> , 125 ppm
	Long-term value: 434 mg/m <sup>3</sup> , 100 ppm
	RFI

### 108-65-6 PM acetate

WEEL 50 ppm

**Additional information:** The International Agency for Research on Cancer has evaluated ethylbenzene and classified it as a possible human carcinogen based on sufficient evidence for carcinogenicity in experimental animals, but

inadequate evidence for cancer in exposed humans. However, a two year rat and mouse gavage study by the National Toxicology Program on mixed xylene isomers including 17% ethylbenzene showed no

evidence of carcinogenicity.

**Protective hygienic** 

measures: Keep away from foodstuffs and animal feed. Wash hands after use.

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases **Breathing equipment:** where short and/or long term overexposure exists, a charcoal filter respirator should be worn. Please

consult an authority on chemical hygeine monitoring if you suspect overexposure conditions exist and

need a specific recommendation on proper ventilation techniques and personal protection.

**Protection of hands:** Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove

recommendation can be given.

(Contd. on page 3)

# Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 11/13/2008 Reviewed on 11/13/2008

Trade name: GOOD GRIP CLEAR

**Eye protection:** Tightly sealed goggles

(Contd. of page 2)

## 9 Physical and chemical properties:

General Information: Odor: Boiling point/Boiling range:	Aromatic -44°C
Flash point:	-19°C
Ignition temperature:	365°C
Auto igniting:	Product is not self-igniting.
Danger of explosion:	Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit.  In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit: Upper Explosion Limit: Vapor Pressure:	1.7 Vol % 10.9 Vol % 40 PSI, 2750 hPa
Density at 20°C: Specific Gravity:	0.76413 g/cm <sup>3</sup> Between 0.77 and 0.85 (Water equals 1.00)
VOC content: VOC content (less exempt solvent MIR value: MIR Value:	519.6 g/l / 4.34 lb/gl ts): 42.7 % 42.7 % 1.46
Solids content:	18.8 %

### 10 Stability and reactivity:

**Conditions to be avoided:** Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.

Possibility of Hazardous

**Reactions:** No dangerous reactions known.

### 11 Toxicological information:

**Primary effect on the skin:** No irritant effect. **Primary effect on the eye:** Irritating effect.

Sensitization:

Additional toxicological

information

information:

No sensitizing effects known.

The product shows the following dangers according to internally approved calculation methods for

preparations:

### 12 Ecological information

Other information: This product does not contain any chloroflourocarbons (CFC's), chlorinated solvents, lead, mercury,

cadmium, hexavalent chromium, polybrominated biphenyl (PBB), or polybrominated diphenyl ether

(PDBE). No specific ecological data is available for this product.

**Acquatic toxicity:** Hazardous for water, do not empty into drains.

## 13 Disposal considerations

DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

**Recommendation:** Completely empty cans should be recycled.

## 14 Transport information:

Hazard class:2.1Identification number:N/ALabel2.1ADR/RID class:2 5F GasesUN-Number:1950

IMDG Class: 2.1
Packaging group: II
EMS Number: F-D,S-U

(Contd. on page 4)

(Contd. of page 3)

# Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 11/13/2008 Reviewed on 11/13/2008

Trade name: GOOD GRIP CLEAR

Marine pollutant: No ICAO/IATA Class: 2.1

**Propper shipping name:** Aerosols, Flammable

Consumer Commodity ORM-D

13	Kegui	ations
	<b>SARA</b>	Sectio

SARA Section 355 (extremely hazardous substances)
None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

1330-20-7 xylene (mix)

108-10-1 methyl isobutyl ketone

100-41-4 ethyl benzene

TSCA (Toxic Substances

Control Act): All ingredients are listed.

## PROPOSITION 65 Chemicals known to cause cancer:

100-41-4 ethyl benzene

Canadian WHMIS: D2A

EPA: A= H

A= Known human carcinogen
B= Probable human carcinogen

C= Possible human carcinogen

D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of

carcinogenicity (or no data is available).

67-64-1	Acetone	I
1330-20-7	xylene (mix)	I
108-10-1	methyl isobutyl ketone	I
100-41-4	ethyl benzene	D

IARC: Group 2

Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of

carcinogenicity.

Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

1330-20-7   xylene (mix)	3
100-41-4 ethyl benzene	2B
9002-88-4 Shamrock texture 5384W 55 mic.	3

ACGIH TLVs: A1-designates a confirmed human carcinogen.

A2-designates a suspected human carcinogen.

A3-designates an animal carcinogen.

A4-designates "not classifiable as a human carcinogen".

67-64-1	Acetone	A4
1330-20-7	xylene (mix)	A4
100-41-4	ethyl benzene	A3

#### NIOSH:

II----I

None of the ingredients is listed.

**Hazard symbols:** Harmful

**Risk phrases:** Extremely flammable.

Harmful by inhalation. Irritating to eyes.

**Safety phrases:** Keep out of the reach of children.

Keep in a cool place.

Keep container in a well-ventilated place.

Keep away from food, drink and animal feedingstuffs. Keep away from sources of ignition - No smoking.

Do not breathe gas/fumes/vapour/spray.

Avoid contact with eyes.

Do not empty into drains, dispose of this material and its container at hazardous or special waste

collection point

If swallowed, seek medical advice immediately and show this container or label.

Use only in well-ventilated areas.

(Contd. on page 5)

# **Material Safety Data Sheet** acc. to ISO/DIS 11014

Printing date 11/13/2008 Reviewed on 11/13/2008

Trade name: GOOD GRIP CLEAR

(Contd. of page 4)

Special labeling of certain

Keep out of the reach of children. preparations:

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Řegulatory Affairs Contact:** 

**Abbreviations and** 

acronyms:

ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Sprace (division of the American Chemical Sprace) CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
VOC: Volatile Organic Compounds (USA, EU)